



CHEMPOINT C/O OCTOCHEM INB WHSE

2090 WAGNER ST  
62471 VANDALIA

USA

**Bostik, Inc.**

BOSTIK US Commonwealth Ohio

4446 Dixie Hwy

45014 FAIRFIELD

Tel No.:

Fax No.:

To :

COA DIST

Email: ChemPointSupplyChain@ChemP

### Certificate of Analysis

inspection certificate 3.1 according to DIN EN 10204

### BOSTIK(R) GLIDECOTE AEROSAL CANS 10.75 OZ/C12

Customer code	: 113357	Bostik order No.	: 2110286911
Product code	: 30603712	Customer order	: PO00118800
Customer Ref.	: 0130742	Delivery No.	: 2140485109
Batch Number	: 25268	Delivered Qty	: 275 COL
Manufact. date	: SEP-26-2025	Delivery date	: OCT-07-2025
Expiration date	: SEP-25-2028		

Method	Property	Unit	Result	Specifications
00700446	SPRAY RATE Q3HY1		1.0200	0.8500 - 1.1500
00700447	EVACUATION Q3HY2	g	311.0000	305.0000 - 322.0000
00700448	PSI AT 70 DEGREES F Q3HY3	lb	34.0000	25.0000 - 37.0000

The Results listed above are certified by our Quality Control Lab:

TECHNICAL INFORMATION AND DATA REGARDING THE COMPOSITION, PROPERTIES OR USE OF THE PRODUCTS DESCRIBED HEREIN IS BELIEVED ACCURATE AS OF THE DATE ABOVE. INFORMATION PROVIDED IN THIS COA IS NOT A GUARANTY OR WARRANTY OF ANY KIND WHATSOEVER.

Customer PO#  
PO301812



# Safety Data Sheet

V207501  
Bostik GlideCote

Revision Date 18-Sep-2015  
Supersedes Date: No information available  
Version 1.02

## SECTION 1: Identification of the Substance/Mixture and of the Company/Undertaking

### 1.1. Product Identifier

Product Name Bostik GlideCote  
Product Code V207501

Product(s) Covered

### 1.2. Relevant Identified Uses of the Substance or Mixture and Uses Advised Against

Recommended use Lubricants, greases, release products.  
Uses Advised Against No information available

### 1.3. Details of the Supplier of the Safety Data Sheet

#### Company Name

Bostik, Inc.  
11320 W. Watertown Plank Road  
Wauwatosa, Wisconsin 53226 USA  
Phone: +1 (800) 843-0844 (Domestic Toll Free)  
Phone: +1 (414) 774-2250 (International)  
Fax: +1 (414) 774-8075  
Email: msds@bostik-us.com

### 1.4. Emergency Telephone Number

Emergency Telephone Telephone: 1-800-227-0332  
(Outside U.S.) 1-703-527-3887

## SECTION 2: Hazards Identification

### 2.1. Classification of the Substance or Mixture

Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
Aspiration toxicity	Category 1
Flammable Aerosol	Category 1

### 2.2. Label Elements

#### EMERGENCY OVERVIEW

**DANGER**


#### Hazard Statements

Causes skin irritation  
Causes serious eye irritation  
May cause drowsiness or dizziness  
May be fatal if swallowed and enters airways  
Extremely flammable aerosol

# Safety Data Sheet

V207501  
Bostik GlideCote

Revision Date 18-Sep-2015  
Supersedes Date: No information available  
Version 1.02



Appearance No information available      Physical State Gas      Odor Solvent

### Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling  
Wear protective gloves/protective clothing/eye protection/face protection  
Avoid breathing dust/fume/gas/mist/vapors/spray  
Use only outdoors or in a well-ventilated area  
Keep away from heat/sparks/open flames/hot surfaces. — No smoking  
Do not spray on an open flame or other ignition source  
Pressurized container: Do not pierce or burn, even after use

### Precautionary Statements - Response

Specific treatment (see first aid measures on this label)  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists; Get medical advice/attention.  
IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.  
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.  
IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

### Precautionary Statements - Storage

Store locked up  
Store in a well-ventilated place. Keep container tightly closed  
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

### Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

### Hazards Not Otherwise Classified (HNOC)

Not applicable

### Unknown Toxicity

1.29% of the mixture consists of ingredient(s) of unknown toxicity

### 2.3. Other Information

May be harmful in contact with skin.

## SECTION 3: Composition/Information on Ingredients

### 3.1 Substances

Not applicable

### 3.2 Mixtures

Chemical Name	CAS No	Weight-%
Acetone	67-64-1	30 - 60
Naphtha, petroleum, light alkylate	64741-66-8	7 - 13
2,2,4-Trimethylpentane	540-84-1	5 - 10

# Safety Data Sheet

V207501  
Bostik GlideCote

Revision Date 18-Sep-2015  
Supersedes Date: No information available  
Version 1.02

Naphtha, petroleum, hydrotreated heavy	64742-48-9	1 - 5
----------------------------------------	------------	-------

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

## SECTION 4: First Aid Measures

### 4.1. Description of First Aid Measures

<b>General Advice</b>	Call 911 or emergency medical service. Remove and isolate contaminated clothing and shoes.
<b>Eye contact</b>	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician.
<b>Skin Contact</b>	In case of contact with liquefied gas, thaw frosted parts with lukewarm water.
<b>Inhalation</b>	Move victim to fresh air. If breathing is irregular or stopped, administer artificial respiration. Administer oxygen if breathing is difficult.
<b>Ingestion</b>	Do NOT induce vomiting. Rinse mouth. Drink plenty of water. If symptoms persist, call a physician. Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Call a physician.
<b>Self-protection of the First Aider</b>	Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

### 4.2. Most Important Symptoms and Effects, Both Acute and Delayed

**Symptoms** No information available.

### 4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

**Note to Physicians** Keep victim warm and quiet.

### 4.4. Reference to Other Sections

**Reference to Other Sections** SECTION 8: Exposure controls/personal protection  
SECTION 11: Toxicological Information

## SECTION 5: Fire Fighting Measures

### 5.1. Extinguishing Media

#### Suitable Extinguishing Media

Use extinguishing agent suitable for type of surrounding fire. Dry chemical or CO2. Water spray, fog or regular foam. Move containers from fire area if you can do it without risk. Damaged cylinders should be handled only by specialists.

#### Unsuitable Extinguishing Media

CAUTION: Use of water spray when fighting fire may be inefficient.

### 5.2. Special Hazards Arising from the Substance or Mixture

#### Specific Hazards Arising from the Chemical

Some may burn but none ignite readily. Ruptured cylinders may rocket.

#### Explosion Data

Sensitivity to Mechanical Impact	None.
Sensitivity to Static Discharge	None.

# Safety Data Sheet

V207501  
Bostik GlideCote

Revision Date 18-Sep-2015  
Supersedes Date: No information available  
Version 1.02

## 5.3. Advice for Firefighters

### **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## **SECTION 6: Accidental Release Measures**

### 6.1. Personal Precautions, Protective Equipment and Emergency Procedures

**Personal Precautions** Remove all possible sources of ignition in the surrounding area. Ensure adequate ventilation, especially in confined areas.

**Other Information** Ventilate the area.

### 6.2. Environmental Precautions

**Environmental Precautions** Use water spray to reduce vapors or divert vapor cloud drift. Avoid allowing water runoff to contact spilled material. Prevent entry into waterways, sewers, basements or confined areas.

### 6.3. Methods and Material for Containment and Cleaning up

**Methods for Containment** If possible, turn leaking containers so that gas escapes rather than liquid. Allow substance to evaporate.

**Methods for Cleaning up** Do not direct water at spill or source of leak.

### 6.4. Reference to other sections

**Reference to Other Sections** SECTION 8: Exposure controls/personal protection  
SECTION 7: Handling and Storage  
SECTION 13: Disposal Considerations

## **SECTION 7: Handling and Storage**

### 7.1. Precautions for Safe Handling

**Advice on Safe Handling** Ensure adequate ventilation, especially in confined areas. Use only in well-ventilated areas. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Pressurized container: Do not pierce or burn, even after use.

### 7.2. Conditions for Safe Storage, including any Incompatibilities

**Storage Conditions** Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Recommended storage temperature. 10 - 35 °C. Observe local regulations / Instructions for storage of pressurized containers.

**Incompatible Materials** None known based on information supplied.

### 7.3. Specific End Use(s)

**Other Information** No information available.

### 7.4. References to Other Sections

# Safety Data Sheet

V207501  
Bostik GlideCote

Revision Date 18-Sep-2015  
Supersedes Date: No information available  
Version 1.02

Reference to Other Sections      SECTION 13: Disposal Considerations  
SECTION 10: Stability and Reactivity

## SECTION 8: Exposure controls/personal protection

### 8.1. Control Parameters

#### Exposure Guidelines

Chemical Name	ACGIH TLV	NIOSH IDLH	OSHA PEL	Mexico
Acetone 67-64-1	STEL: 500 ppm TWA: 250 ppm	IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m <sup>3</sup>	TWA: 1000 ppm TWA: 2400 mg/m <sup>3</sup>	TWA: 1000 ppm TWA: 2400 mg/m <sup>3</sup> STEL: 1260 ppm STEL: 3000 mg/m <sup>3</sup>
2,2,4-Trimethylpentane 540-84-1	TWA: 300 ppm	-	-	-

Chemical Name	Argentina	Brazil	Chile	Venezuela
Acetone 67-64-1	TWA: 500 ppm STEL: 750 ppm	TWA: 780 ppm TWA: 1870 mg/m <sup>3</sup>	TWA: 600 ppm TWA: 1424 mg/m <sup>3</sup>	STEL: 750 ppm TWA: 500 ppm
2,2,4-Trimethylpentane 540-84-1	TWA: 300 ppm	-	-	-

### 8.2. Exposure Controls

**Engineering Controls**                      Ensure adequate ventilation, especially in confined areas.

#### Personal protective equipment [PPE]

- Eye/Face Protection**                      Tight sealing safety goggles. Face protection shield.
- Skin and Body Protection**                Wear suitable chemical resistant gloves. The selection of suitable gloves does not only depend on the material, but also on further marks of quality and various manufacturers.
- Respiratory Protection**                    If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.
- General Hygiene Considerations**        When using do not eat, drink or smoke. Regular cleaning of equipment, work area and clothing is recommended.

## SECTION 9: Physical and Chemical Properties

### 9.1. Information on Basic Physical and Chemical Properties

**Physical State**                                      Gas  
**Color**                                                      Colorless  
**Odor**                                                        Solvent  
**Odor Threshold**                                      No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No information available	
Melting Point/Freezing Point	No information available	
Boiling Point	No information available °C / °F	
Flash Point	-92 °C / -133.6 °F	
Evaporation Rate	No information available	
Flammability (solid, gas)	No information available	
Flammability Limit in Air		
Upper Flammability Limit	No information available	
Lower Flammability Limit	No information available	

# Safety Data Sheet

V207501  
Bostik GlideCote

Revision Date 18-Sep-2015  
Supersedes Date: No information available  
Version 1.02

Vapor Pressure	No information available
Vapor Density	No information available
Specific Gravity	No information available
Water Solubility	No information available
Solubility in Other Solvents	
Partition Coefficient	No information available
Autoignition Temperature	No information available
Decomposition Temperature	No information available
Kinematic Viscosity	No information available
Dynamic Viscosity	No information available
Explosive Properties	No information available
Oxidizing Properties	No information available

## 9.2. Other Information

Softening Point	No information available
Molecular Weight	No information available
Solvent Content (%)	No information available
Solid Content (%)	2.3
Density	.8 g/ml
VOC	20 %

## SECTION 10: Stability and Reactivity

### 10.1. Reactivity

None under normal use conditions.

### 10.2. Chemical Stability

Stable under recommended storage conditions.

### 10.3. Possibility of Hazardous Reactions

None under normal processing.

### 10.4. Conditions to Avoid

Heating causes rise in pressure with risk of bursting.

### 10.5. Incompatible Materials

None known based on information supplied.

### 10.6. Hazardous Decomposition Products

None known based on information supplied.

## SECTION 11: Toxicological Information

### 11.1. Information on Toxicological Effects

Product Information	No Data Available
Inhalation	No Data Available.
Eye contact	No Data Available.
Skin Contact	No Data Available.
Ingestion	No Data Available.

### Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Acetone	= 5800 mg/kg ( Rat )	>15800 mg/Kg (rat)	= 50100 mg/m <sup>3</sup> ( Rat ) 8 h

# Safety Data Sheet

V207501  
Bostik GlideCote

Revision Date 18-Sep-2015  
Supersedes Date: No information available  
Version 1.02

67-64-1			
Naphtha, petroleum, light alkylate 64741-66-8	> 7000 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	> 5.04 mg/L ( Rat ) 4 h
2,2,4-Trimethylpentane 540-84-1	> 2500 mg/kg ( Rat )	-	= 47.4 mg/L ( Rat ) 1 h
Naphtha, petroleum, hydrotreated heavy 64742-48-9	> 5000 mg/kg ( Rat )	> 3160 mg/kg ( Rabbit )	-

## Delayed and Immediate Effects as well as Chronic Effects from Short and Long-term Exposure

<b>Symptoms</b>	No information available.
<b>Skin Corrosion/Irritation</b>	No information available.
<b>Serious Eye Damage/Eye Irritation</b>	No information available.
<b>Irritation</b>	No information available.
<b>Corrosivity</b>	No information available.
<b>Sensitization</b>	No information available.
<b>Germ Cell Mutagenicity</b>	No information available.
<b>Reproductive Toxicity</b>	No information available.
<b>Developmental Toxicity</b>	No information available.
<b>Teratogenicity</b>	No information available.
<b>STOT - Single Exposure</b>	No information available.
<b>STOT - Repeated Exposure</b>	No information available.
<b>Chronic Toxicity</b>	Avoid repeated exposure.
<b>Target Organ Effects</b>	Central nervous system, Eyes, Respiratory system, Skin.
<b>Aspiration Hazard</b>	No information available.
<b>Carcinogenicity</b>	This product does not contain any carcinogens or potential carcinogens as listed by ACGIH, OSHA, IARC or NTP at or above 0.1 wt%.

## SECTION 12: Ecological Information

### 12.1. Toxicity

Chemical Name	Algae/Aquatic Plants	Fish	Toxicity to Microorganisms	Crustacea
Acetone 67-64-1		LC50 96 h 4.74 - 6.33 mL/L (Oncorhynchus mykiss ) LC50 96 h 6210 - 8120 mg/L (Pimephales promelas static) LC50 96 h = 8300 mg/L (Lepomis macrochirus )	EC50 = 14500 mg/L 15 min	EC50 48 h 10294 - 17704 mg/L (Daphnia magna Static) EC50 48 h 12600 - 12700 mg/L (Daphnia magna )
Naphtha, petroleum, light alkylate 64741-66-8	EC50 72 h = 6.4 mg/L (Pseudokirchneriella subcapitata)			LC50 48 h = 2 mg/L (Mysidopsis bahia )
Naphtha, petroleum, hydrotreated heavy 64742-48-9		LC50 96 h = 2200 mg/L (Pimephales promelas )		LC50 96 h = 2.6 mg/L (Chaetogammarus marinus )

### 12.2. Persistence and Degradability

No information available.

### 12.3. Bioaccumulative Potential

# Safety Data Sheet

V207501  
Bostik GlideCote

Revision Date 18-Sep-2015  
Supersedes Date: No information available  
Version 1.02

No information available.

## 12.4. Mobility in Soil

No information available.

## 12.5 Other adverse effects

No information available

## **SECTION 13: Disposal Considerations**

### 13.1. Waste Treatment Methods

#### **Disposal of Wastes**

It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations

#### **Contaminated Packaging**

Dispose of in accordance with federal, state and local regulations

## **SECTION 14: Transport Information**

### **Note:**

Per 49 CFR 173.306(a)(3), our aerosol product is considered a Limited Quantity for all modes of transportation and ORM-D no longer applies to the product

### DOT

UN/ID No	UN1950
Proper Shipping Name	Aerosols
Hazard Class	2.1
Special Provisions	N82
Description	UN1950, Aerosols, 2.1,
Emergency Response Guide Number	126

### IATA

UN/ID No	UN1950
Proper Shipping Name	Aerosols, flammable
Hazard Class	2.1
ERG Code	10L
Special Provisions	A145, A167
Description	UN1950, Aerosols, flammable, 2.1

### IMDG

UN/ID No	UN1950
Proper Shipping Name	Aerosols
Hazard Class	2
EmS-No	F-D, S-U
Special Provisions	190, 277, 327, 344, 63, 959
Description	UN1950, Aerosols, 2

## **SECTION 15: Regulatory Information**

### Global Inventories

TSCA	Listed
DSL	Listed

# Safety Data Sheet

V207501  
Bostik GlideCote

Revision Date 18-Sep-2015  
Supersedes Date: No information available  
Version 1.02

## Legend:

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL** - Canadian Domestic Substances List

**Listed** - The components of this product are either listed or exempt from listing on inventory.

**Not Listed** - One or more components of this product are not listed on inventory.

## Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR

## WHMIS Hazard Class

A - Compressed gases

B5 - Flammable aerosol

D2B - Toxic materials



## United States of America

## SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

## California Proposition 65

This product does not contain one or more substances listed on Proposition 65 at or above 0.01 wt. %.

## Europe

### Restrictions of Use of Hazardous Substances (RoHS) Directive 2011/65/EU

This product does not contain Lead (7439-92-1), Cadmium (7440-43-9), Mercury (7439-97-6), Hexavalent chromium (7440-47-3), Polybrominated biphenyls (PBB), and Polybrominated diphenyl ethers (PBDE) above the regulated limit mentioned in this regulation.

### EU-REACH (1907/2006) - Candidate List of Substances of Very High Concern (SVHC) for Authorization in accordance with Article 59

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

## SECTION 16: Other Information

**HMIS**                      Health Hazards 2              Flammability 4              Physical Hazards 0              Personal Protection X

### Key or Legend to Abbreviations and Acronyms Used in the Safety Data Sheet

No information available

### Key Literature References and Sources for Data

No information available

Prepared By                      Product Safety & Regulatory Affairs

Revision Date                      18-Sep-2015

Revision Note                      Not applicable.

# Safety Data Sheet

V207501  
Bostik GlideCote

Revision Date 18-Sep-2015  
Supersedes Date: No information available  
Version 1.02

---

**Training Advice** No information available

**Further Information** No information available

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**

Customer PO#  
PO301812